



### Features:

- Low maintenance sealed unit
- Gel filled reference cell
- BNC connection with Boot plastic Cover
- Cable length 5 meter
- Ceramic Diaphragm high accuracy

### Field Application:

- General laboratory
- Drinking Water
- Swimming pools
- Water monitoring and control plan

### Features:

- Range: pH 2÷12
- Temperature: 0÷60 °C
- Pressure: 6 Bar
- Trasparten plastic Body
- **Single junction** with KCL Gel and **Ceramic diaphragm**.
- BLUE cup with **5 meters cable** size 3mm, BNC plug included with blue Boot cup.
- Batch production with 4 number to indicate Week and Year production.
- Single Package with neutral carton box.
- Neutral Label.

## TECHNICAL CHARACTERISTICS

pH Range:	2 ÷ 12
Min. Conductivity:	50 µS/cm
Temp. Range:	60° C
Pressure Range:	up to 6 bar
Body material:	Epoxy
Membrane material:	Glass
Diaphragm type:	one Ceramic
Mechanical Mounting:	Ø 12
Electrical Connection:	5 m cable + BNC (Blue BOOT Cup)
Reference:	GEL
Storage temperature	+2 ÷50 °C ( <b>do not freeze</b> )

## DIMENSIONS

